

GO Switch Models 71 - 77

Model	Contact Form	Sensing Range	Outlet Position	Enclosure Material	Approvals	Wiring Options
71 3/8" x 3 15/16" 1/2" NPT	<input checked="" type="checkbox"/> 1 SPDT	<input checked="" type="checkbox"/> 3 Standard sensing .100" end sensing (Models 73-77) (Enclosure must be 2 or 6)	2 Side entry with teflon™ leads (Models 72, 74, & 76) (Approval must be 2 or 8 and Wiring must be F)	<input checked="" type="checkbox"/> 2 303 stainless steel (rated 2,000 psi) (Sensing must be 3)	2 HiTemp to 400°F; (Wiring must be F)	Lead Wires - 18 gauge PVC insulated <input checked="" type="checkbox"/> A2 36" A3 72" A4 144" A _ _ _
71M M12 x 1				3 HiPressure - 303 stainless steel (rated 5,000 psi) (Models 73-77) Sensing must be 4 and Approval must be 2, 7, 8, or 9)	<input checked="" type="checkbox"/> 3 UL Cl I Div 1 & 2 Grps A-D; Cl II Div 1 & 2, Grps E-G (Models 71, 73, 75 & 77) (Wiring A, B, or F) (Lead seal req'd within 18")	Cable - 18 Gauge PVC insulated <input checked="" type="checkbox"/> B2 36" B3 72" B4 144" B _ _ _
72 3/8" x 3 3/8" No conduit		4 .072" end sensing (Models 73-77) (Enclosure must be 3 and Approvals must be 2, 7, 8, or 9)	<input checked="" type="checkbox"/> 5 Bottom of enclosure	4 HiPressure - 303 stainless steel (rated 10,000 psi) (Models 73-76) Sensing must be 5 and Approval must be 2, 7, 8, or 9)	<input checked="" type="checkbox"/> 4 CSA Cl I Div 1; Grps A-D; Cl II Div 1, Grps E-G; Cl III (Models 71, 73, 75 & 77) (Wiring A, B, or F) (Lead seal req'd within 18")	Water Resistant Squeeze Connector PVC insulated (Models 72, 74, 76) C2 36" C3 72" C4 144" C _ _ _
<input checked="" type="checkbox"/> 73 5/8" x 3 5/8" 1/2" NPT		5 .060" end sensing (Models 73-77) (Enclosure must be 4 and Approvals must be 2, 7, 8, or 9)		6 316 stainless steel (rated 2,000 psi)	<input checked="" type="checkbox"/> 6 CSA Cl I, Div 2; Grps A-D; Cl II, Div 2; Grps E-G; Cl III (Models 71, 73, 75 & 77) (Wiring A, B, or F) (Lead seal req'd within 18")	Quick Disconnect Mini Connector (Approval must be 7 or 8; 3 pin is 8 only) <input checked="" type="checkbox"/> DCA 3 pin DCD 4 pin DCG 5 pin
73M M18 x 1				7 HiPressure - 303 stainless steel (rated 3,500 psi) (Model numbers must be: 73-14573-XX 75-14573-XX A or B termination only)	7 CSA General Purpose	Micro Connector (Approval must be 7 or 8; 3 pin is 8 only) <input checked="" type="checkbox"/> DBA 3 pin DBD 4 pin DBG 5 pin
<input checked="" type="checkbox"/> 74 5/8" x 2 3/4" No conduit		6 .040" end sensing (Models 71 & 72)			<input checked="" type="checkbox"/> 8 UL General Purpose	SubSea Connector (Models 73, 75 & 77) 3DD 3 pin 4DD 4 pin 3DE 3 pin 90° 4DE 4 pin 90°
74M M18 x 1					9 CENELEC: EEx d IIC T6 Zone 1. (Models 73, 75, & 77) (Wiring must be A or B)	Hi-Temp Leads (18 gauge teflon™ insulated) F2 36" F3 72" F4 144" F _ _ _
75 5/8" x 4 5/16" 1/2" NPT					T ATEX Zone 1 EEx d IIC; II 2G T6 (-20°C to +50°C), (Model 73 only) (For HiTemp to +150°C use Wiring H)	Hi-Temp Leads (18 gauge peek insulated) H2 36" H3 72" H4 144" H _ _ _
75M M18 x 1						
76 5/8" x 3 3/16" No conduit						
76M M18 x 1						
77 3/4" x 5 13/16" 1/2" NPT						

Ordering Guide
Fill in the boxes to create
your 'ordering number.'

Model	Contact Form	Sensing Range	Outlet Position	Enclosure Material	Approvals	Wiring Options
-------	--------------	---------------	-----------------	--------------------	-----------	----------------