

# GO Switch Model 81

Model	Contact Form	Sensing Range	Outlet Position	Enclosure Material	Approvals	Wiring Options
<p><input checked="" type="checkbox"/> <b>81</b> 1 1/2" square x 4 7/8" overall. Subtract 1/2" from length for side outlet</p>	<p><b>1</b> SPDT (Form C)</p> <p><input checked="" type="checkbox"/> <b>2</b> DPDT (Form CC)</p>	<p><input checked="" type="checkbox"/> <b>0</b> Approx. 1/4" end sensing</p>	<p><b>1</b> Side outlet</p> <p><input checked="" type="checkbox"/> <b>5</b> Bottom of enclosure</p>	<p><input checked="" type="checkbox"/> <b>1</b> Brass - coated with flat black lacquer</p> <p><input checked="" type="checkbox"/> <b>2</b> Stainless steel**</p> <p><b>3</b> Brass - corrosion resistant coating (polyurethane)</p> <p><b>4</b> Stainless steel** - corrosion resistant coating (polyurethane)</p> <p><small>**Stainless steel switches are recommended for wet or harsh environments.</small></p>	<p><b>2</b> High temperature to 350°F (176°C) with Teflon™ leads (Wiring must be F) (Enclosure must be 2 or 4)</p> <p><b>3</b> UL CI I, Div 1 &amp; 2; Grps A-D; CI II, Div 1 &amp; 2, Grps E-G; CI III (Enclosure must be 2 or 4) (Wiring must be A, B, or F) (Lead seal req'd within 18")</p> <p><input checked="" type="checkbox"/> <b>4</b> CSA CI I, Div 1; Grps A-D; CI II, Div 1, Grps E-G; CI III. (Enclosure must be 2 or 4) (Wiring must be A, B, or F) (Lead seal req'd within 18")</p> <p><input checked="" type="checkbox"/> <b>6</b> CSA CI I, Div 2; Grps A-D; CI II, Div 2, Grps E-G; CI III; (Wiring must be A, B, or F) (Lead seal req'd within 18")</p> <p><b>7</b> CSA certified General Purpose</p> <p><b>8</b> UL listed General Purpose</p>	<p><b>Lead Wires</b> - 18 gauge PVC insulated</p> <p><input checked="" type="checkbox"/> <b>A2</b> 36"</p> <p><b>A3</b> 72"</p> <p><b>A4</b> 144"</p> <p><b>A</b> _ _ _</p> <p><b>Cable</b> - 18 gauge PVC insulated (Contact form must be 1)</p> <p><b>B2</b> 36"</p> <p><b>B3</b> 72"</p> <p><b>B4</b> 144"</p> <p><b>B</b> _ _ _</p> <p><b>Quick Disconnect Mini Connector</b> (Approval must be 7 or 8; 3 pin is 8 only)</p> <p><b>DCA</b> 3 pin</p> <p><b>DCD</b> 4 pin</p> <p><b>DCG</b> 5 pin</p> <p><b>DCH</b> 7 pin</p> <p><b>SubSea Connector</b> (Approval must be 7 or 8; (Enclosure must be 2 or 4)</p> <p><b>3DD</b> 3 pin</p> <p><b>4DD</b> 4 pin</p> <p><b>8DD</b> 8 pin</p> <p><b>3DE</b> 3 pin 90°</p> <p><b>4DE</b> 4 pin 90°</p> <p><b>Hi-Temp Leads</b> (18 gauge teflon™ insulated)</p> <p><b>F2</b> 36"</p> <p><b>F3</b> 72"</p> <p><b>F4</b> 144"</p> <p><b>F</b> _ _ _</p>
<p><b>Model</b> <b>81</b></p>	<p><b>Contact Form</b></p>	<p><b>Sensing Range</b></p>	<p><b>Outlet Position</b></p>	<p><b>Enclosure Material</b></p>	<p><b>Approvals</b></p>	<p><b>Wiring Options</b></p>

**Ordering Guide**  
Fill in the boxes to create your 'ordering number.'