

Defender - Turbine Trip Switch

Model	GO Switches	Wiring Options
<p>✔ 48 Defender Turbine Valve Monitoring System</p> <p>Heavy Duty 11 Gauge Steel 12" x 10" x 5" - ANSI 61 Light Gray</p>	<p>Model 74-LLS: SPDT, environmentally sealed, rated 4A @ 120VAC, 3A @ 24VDC, maximum, with prewired HiTemp™ Teflon lead wires</p> <p>Choose number of switches (minimum 1, maximum 10)</p> <p>010000 (1) Leverless Limit Switch 020000 (2) Leverless Limit Switches 030000 (3) Leverless Limit Switches 040000 (4) Leverless Limit Switches 050000 (5) Leverless Limit Switches 060000 (6) Leverless Limit Switches ✔ 070000 (7) Leverless Limit Switches 080000 (8) Leverless Limit Switches 090000 (9) Leverless Limit Switches 100000 (10) Leverless Limit Switches</p>	<p>✔ 00 Male/Female Mil Spec Quick Disconnect with back shell connection to 1-1/4" flex conduit</p> <p>01 Male/Female Mil Spec Quick Disconnect with 25 ft. cable 02 Male/Female Mil Spec Quick Disconnect with 50 ft. cable 03 Male/90° Female Mil Spec Quick Disconnect with back shell connection to 1-1/4" flex conduit 04 Male/90° Female Mil Spec Quick Disconnect with 25 ft. cable 05 Male/90° Female Mil Spec Quick Disconnect with 50 ft. cable 06 Male/45° Female Mil Spec Quick Disconnect with back shell connection to 1-1/4" flex conduit 07 Male/45° Female Mil Spec Quick Disconnect with 25 ft. cable 08 Male/45° Female Mil Spec Quick Disconnect with 50 ft. cable 10 Male/90° Female Mil Spec Quick Disconnect with 25 ft. of HiTemp™ cable 12 Male/Female Mil Spec Quick Disconnect with 75 ft. cable 13 Male/90° Female Mil Spec Quick Disconnect with 100 ft. cable 16 Male/90° Female Mil Spec Quick Disconnect with 50 ft. of HiTemp™ cable</p>
<p>Model 48</p>	<p>GO Switches</p>	<p>Wiring Options</p>

Ordering Guide

Fill in the boxes to create your 'ordering number.'